True Presence Multisensor KNX



EAN 4007841 056353























Function description

7 senses for intelligent buildings. Besides human presence, True Presence® Multisensor KNX also makes it possible to measure brightness, room temperature, humidity, air quality, volatile organic compounds (VOC) and CO2. Nothing remains hidden from the True Presence® Multisensor KNX. Result: better efficiency, better health, better safety and better comfort.

True Presence Multisensor KNX



EAN 4007841 056353

Technical specifications

Туре	Presence detector
Dimensions (L x W x H)	33 x 123 x 123 mm
Mains power supply	30 V
Power consumption	1 W
Sensor Technology	Multisensor
Application, place	Indoors
Application, place, room	classroom, lecture hall, one-person office, open-plan office, conference room / meeting room, hotel room, care room, duty room, recreation room, sports hall, reception / lobby, Indoors
Installation site	ceiling
Installation	Concealed wiring
HF-system	7,2 GHz
Electronic scalability	Yes
Mechanical scalability	No
Mounting height	2 – 12 m
Optimum mounting height	2,8 m
Detection angle	360 °
Angle of aperture	360 °
Reach, radial	Ø 15 m (177 m²)
Reach, tangential	Ø 15 m (177 m²)

Reach, presence	Ø 15 m (177 m²)
True Presence reach	Ø 9 m (64 m²)
Twilight setting TEACH	Yes
Twilight setting	1 – 1000 lx
Time setting	0 s – 1092 min
Basic light level function	Yes
KNX functions	Comfort, CO2, Photo-cell controller, Basic light level function, Light level, HVAC output, Constant-lighting control, Light output 4x, Air pressure, Humidity output, Presence output, Day / night function, Dewpoint, VOC, Temperature output
With bus coupling	Yes
Settings via	ETS software, Bluetooth, Bus
With remote control	No
Interconnection	Yes
IP-rating	IP20
Material	Plastic
Ambient temperature	0 – 40 °C
Colour	white
Colour, RAL	9010
Manufacturer's Warranty	5 years
PU1, EAN	4007841056353

Accessories


EAN 4007841 063870 Surface-mounting adapter for Multisensor

True Presence Multisensor KNX



EAN 4007841 056353

Detection Zone



Mögliche Montagehöhe: 2,00 m – 12,00 m Orange: True Presence Schwarz: Bewegung und Präsenz

Dimension Drawing

